



## Mobil 75W MULTI-VEHICLE

Mobil Passenger Vehicle Lube  
Manual Gear Oil

### Product Description

Mobil 75W Multi Vehicle is a manual gear oil fluid with excellent bearing and gear protection and proven synchroniser performance in a wide range of applications. Its versatility of use is a plus for workshops aiming to ensure an optimal service to their customers while simplifying their operations and product management.

### Features and Benefits

- High Fleet coverage to reduce inventory.
- Advanced friction profile and proven synchroniser performance for smooth shifting.
- Robust corrosion protection to ensure lifetime of parts.
- Maintains performance at low temperatures. Critical to ensure protection at start up.
- Excellent cleanliness to reduce deposits that may affect seals/leaks, wear, and poor shifting.

### Applications

Recommended for a variety of BMW, Ford, Land Rover & VAG group applications and generally where a 75W, API GL-4 oil is specified. To ensure correct oil selection check the latest application recommendations on the Mobil Product Selector:

<https://www.mobil.co.uk/en-gb/b2c-product-selector/>

This product is recommended for use in applications requiring BMW MTF LT-3; Ford WSS-M2C200-D2; GM 19259104 (BOT 303); VW G 052 178; VW G 060 726; VW G 052 171; VW G 052 726; VW G 052 512; VW G 070 726 A2; VW G 052 527 A2; VW G 055 512; BOT 350 M3.

OEM Vehicle Marque	Quality Level The product is recommended for use in applications requiring:
Aston Martin	API: GL-4 SAE 75W
Audi (EU)	VW G 052 171/178/512/527/726, VW G 055 512, VW G 060 726, VW G 070 726
Austin	API: GL-4 SAE 75W
BMW (EU)	BMW MTF LT-3
Chevrolet (EU) (Daewoo)	GM 19259104/GM 19259105 (BOT 303)
Cupra	VW G 052 527
Daihatsu	API: GL-4 SAE 75W
Ford (EU)	Ford M2C200-D2
Hyundai (EU)	API: GL-4 SAE 75W
Jaguar	Ford M2C200-D2
Lamborghini	VW G 052 171
Land Rover (EU)	Ford M2C200-D2
LDV	API: GL-4 SAE 75W
MAN	VW G 052 527
Mazda (EU)	Ford M2C200-D2
MINI (EU)	BMW MTF LT-3
Mitsubishi (EU)	API: GL-4 SAE 75W
Morgan	BMW MTF LT-3
Nissan (EU)	API: GL-4 SAE 75W
Renault	API: GL-4 SAE 75W
Saab	API: GL-4 SAE 75W
Seat	VW G 052 171/178/512/527/726, VW G 055 512, VW G 060 726, VW G 070 726
Skoda	VW G 052 171/178/512/527/726, VW G 055 512, VW G 060 726, VW G 070 726
Subaru (EU)	API: GL-4 SAE 75W
Suzuki	API: GL-4 SAE 75W
Toyota (EU)	API: GL-4 SAE 75W
UAZ	API: GL-4 SAE 75W
Volkswagen (VW) (EU)	VW G 052 171/178/512/527/726, VW G 055 512, VW G 060 726, VW G 070 726
Volvo (EU)	Special transmission oil, Castrol BOT 350 M3

**Typical Inspection Data**

Density @ 20 °C	0.848 g/cm <sup>3</sup>
Viscosity @ 100 °C	6.9 cSt
Viscosity @ 40 °C	37 cSt
Calcium	0.29%
Phosphorus	0.05%
Colour	Brown
Pour Point	-39 °C

**Note**

The data contained in this publication is based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, this data does not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.

**Health and safety**

Health and safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <https://www.mobil-ancillaries.com>

Terms & Conditions: © 2021. All rights reserved to Moove Lubricants Ltd. Mobil and Mobil products named in this material are registered brands and trademarks of Exxon Mobil Corporation or one of its subsidiaries, licensed for use to Moove Lubricants Ltd who are responsible for this document and the use of such trademarks within it.

No part of this document or any trademark is permitted to be copied, reproduced or otherwise used or applied without prior consent. Manufactured by Moove Lubricants Ltd.

Operations Plant Dering Way, Gravesend, Kent DA12 2QX +44 (0) 1474 564 311

Energy lives here™

**ExxonMobil**

Exxon Mobil ESSO XTO

© Copyright 2003-2021 Exxon Mobil Corporation.

All Rights Reserved